## NSN 5305-00-512-5278

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-512-5278

| View Online at https://aerobasegroup.com/nsn/5305-00-512-5278        |
|--|
| Thread Class:  |
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| Between 0.251 inches and 0.301 inches                                |
| Fastener Length:   |
| Between 2.261 inches and 2.291 inches                                |
| Head Style:  |
| Flat countersunk   |
| Head Diameter:   |
| Between 0.338 inches and 0.381 inches                                |
| Grip Diameter:   |
| Between 0.1885 inches and 0.1895 inches                              |
| Shank Unthreaded Hole Diameter:                                      |
| 0.070 inches and 0.080 inches first hole                             |
| Internal Drive Style:  |
| High-torque  |
| Thread Diameter:   |
| 0.190 inches   |
| Grip Length:   |
| Between 1.990 inches and 2.010 inches                                |
| Thready Qty Per Inch (tpi):  |
| 32   |
| Min. Tensile Strength (psi):   |
| 160000 pounds per square inch  |
| Hardness Rating:   |
| 36.0 rockwell c and 40.0 rockwell c                                  |
| Countersink Angle:   |
| Between 99.0 degrees and 101.0 degrees                               |
| Distance From Head Largest Bearing Surface To Shank Hole Center:     |
| 2.134 inches and 2.184 inches first hole                             |
| Product Name:  |
| Navy special project   |
| Material:  |
| Steel comp e4340 or steel comp 8740                                  |
| Surface Treatment:   |
| Cadmium and chromate   |
| Surface Treatment Specification:                                     |
| Qq-p-416, type 2, cl 2 federal specification all treatment responses |
| Thread Series Designator:  |

Unjf

## NSN 5305-00-512-5278

Close Tolerance Screw - Page 2 of 2



| _ |   |   |     | - |      |  |
|---|---|---|-----|---|------|--|
| C | h | Δ | Iŧ. |   | ife: |  |
|   |   |   |     |   |      |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0