NSN 5305-00-512-6103

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-512-6103 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.278 inches and 0.329 inches **Fastener Length:** Between 1.481 inches and 1.501 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.477 inches and 0.492 inches **Head Height:** Between 0.126 inches and 0.141 inches **Grip Diameter:** Between 0.2487 inches and 0.2492 inches **Shank Unthreaded Hole Diameter:** 0.076 inches first hole and 0.086 inches first hole **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.062 inches and 1.078 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 1.395 inches first hole and 1.411 inches first hole **Surface Finish:** 63.0 microinches grip **Special Features:** Retaining balls in shank Material: Steel **Surface Treatment: Thread Series Designator:**

Passivate
Thread Series Designato
Unjf
Shelf Life:
N/a

NSN 5305-00-512-6103

Close Tolerance Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0