## NSN 5305-00-512-6360

Close Tolerance Screw - Page 1 of 2

**Thread Class:** 

View Online at https://aerobasegroup.com/nsn/5305-00-512-6360



## 3a **Thread Direction: Right-hand Thread Length:** Between 0.277 inches and 0.328 inches Fastener Length: Between 3.793 inches and 3.813 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.477 inches and 0.492 inches **Head Height:** Between 0.126 inches and 0.141 inches **Grip Diameter:** Between 0.2487 inches and 0.2492 inches Shank Unthreaded Hole Diameter: 0.076 inches first hole and 0.086 inches first hole **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Grip Length: Between 3.375 inches and 3.391 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 3.708 inches and 3.724 inches first hole Surface Finish: 63.0 microinches grip **Product Name:** Navy special project **Special Features:** Retaining balls in shank Material: Steel Surface Treatment: Passivate **Thread Series Designator:**

Unjf

## NSN 5305-00-512-6360

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

