NSN 5305-00-512-6417

Close Tolerance Screw - Page 1 of 2

Thread Class:

View Online at https://aerobasegroup.com/nsn/5305-00-512-6417



3a **Thread Direction: Right-hand Thread Length:** Between 0.277 inches and 0.328 inches Fastener Length: Between 5.668 inches and 5.688 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.477 inches and 0.492 inches **Head Height:** Between 0.126 inches and 0.141 inches **Grip Diameter:** Between 0.2487 inches and 0.2492 inches Shank Unthreaded Hole Diameter: 0.076 inches first hole and 0.086 inches first hole **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Grip Length: Between 5.250 inches and 5.266 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 5.583 inches first hole and 5.599 inches first hole Surface Finish: 63.0 microinches grip **Special Features:** Retaining balls in shank Material: Steel Surface Treatment: Passivate **Thread Series Designator:** Unjf Shelf Life: N/a

NSN 5305-00-512-6417

Close Tolerance Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

