NSN 5305-00-512-6428

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-512-6428 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.262 inches and 0.313 inches **Fastener Length:** Between 0.262 inches and 0.313 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.360 inches and 0.374 inches **Head Height:** Between 0.095 inches and 0.110 inches **Grip Diameter:** Between 0.1889 inches and 0.1894 inches **Shank Unthreaded Hole Diameter:** 0.070 inches first hole and 0.080 inches first hole **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches **Grip Length:** Between 1.017 inches and 1.048 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 1.231 inches first hole and 1.247 inches first hole **Surface Finish:** 63.0 microinches grip **Product Name:** Navy special project Material: Iron alloy 660 **Material Specification:** Ams 5732 assn standard single material response

Surface Treatment:
Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

NSN 5305-00-512-6428

Close Tolerance Screw - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0