

View Online at <https://aerobasegroup.com/nsn/5305-00-512-6428>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.262 inches and 0.313 inches

Fastener Length:

Between 0.262 inches and 0.313 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.360 inches and 0.374 inches

Head Height:

Between 0.095 inches and 0.110 inches

Grip Diameter:

Between 0.1889 inches and 0.1894 inches

Shank Unthreaded Hole Diameter:

0.070 inches first hole and 0.080 inches first hole

Internal Drive Style:

Slot

Thread Diameter:

0.190 inches

Grip Length:

Between 1.017 inches and 1.048 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.231 inches first hole and 1.247 inches first hole

Surface Finish:

63.0 microinches grip

Product Name:

Navy special project

Material:

Iron alloy 660

Material Specification:

Ams 5732 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0