## NSN 5305-00-512-6430

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-512-6430 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.277 inches and 0.328 inches **Fastener Length:** Between 1.356 inches and 1.376 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.477 inches and 0.492 inches **Head Height:** Between 0.126 inches and 0.141 inches **Grip Diameter:** Between 0.2487 inches and 0.2492 inches **Shank Unthreaded Hole Diameter:** 0.076 inches and 0.086 inches first hole **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.048 inches and 1.079 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 1.271 inches and 1.287 inches first hole **Surface Finish:** 63.0 microinches grip **Product Name:** Navy special project Material: Iron alloy 660

## **Material Specification:**

Ams 5732 assn standard single material response

**Surface Treatment:** 

**Passivate** 

**Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

## NSN 5305-00-512-6430

Close Tolerance Screw - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No Fiig:

A003b0