Externally Relieved Body Screw - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-512-6484

| iread Class:   |   |
|--|---|
|  |   |
|  |   |
| aread Direction:   |   |
| ght-hand   |   |
| read Length:   |   |
| etween 0.230 inches and 0.270 inches   |   |
| stener Length:   |   |
| tween 0.610 inches and 0.630 inches  |   |
| ead Style:   |   |
| an   |   |
| ead Diameter:  |   |
| tween 0.306 inches and 0.322 inches  |   |
| ead Height:  |   |
| etween 0.105 inches and 0.115 inches   |   |
| rst Diameter From Head:  |   |
| etween 0.115 inches and 0.135 inches   |   |
| stance From Largest Bearing Surface Of Head To End Of First Diameter:                |   |
| etween 0.340 inches and 0.400 inches   |   |
| ternal Drive Style:  |   |
| oss recess type 1  |   |
| read Diameter:   |   |
| 164 inches   |   |
| ready Qty Per Inch (tpi):  |   |
|  |   |
| n. Tensile Strength (psi):   |   |
| 000 pounds per square inch   |   |
| ternally Relieved Body Diameter Quantity:  |   |
|  |   |
| aterial:   |   |
| eel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 | 6 |
| Irface Treatment:  |   |
| assivate   |   |
| rread Series Designator:   |   |
| nc   |   |
| nelf Life:   |   |
| a  |   |
| nit Of Measure:  |   |
|  |   |
| emilitarization:   |   |
|  |   |
| ig:  |   |
| 9.<br>)03b0  |   |
|  |   |