NSN 5305-00-514-0383

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-514-0383

view Online at https://aerobasegroup.com/hsh/5505-00-514-0505
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.580 inches
Fastener Length:
1.020 inches
Head Style:
Flat chamfer
Head Diameter:
0.408 inches
Head Height:
0.390 inches
Locking Feature:
Locking teeth threads
Internal Drive Style:
W/o internal drive
End Application:
1005-00-322-9716
Thread Diameter:
0.375 inches
Thready Qty Per Inch (tpi):
16
Special Features:
Head has hole threaded to no.10-32unf-2b; 24 serrations; pitch dia.=0.3906 in.; heat treatment: carburize at 1600-1650 deg. F. To case
depth of 0.004-0.006 in., oil quench, temper at 350 deg. F. For 30 min.
Material:
Steel
Material Specification:
Astm a108, cmpsn 1018-1022, 1117 or 1118 assn standard single material response
Surface Treatment:
Phosphate manganese or phosphate zinc
Surface Treatment Specification:
Mil-p-16232, type m, class 1 military specification single treatment response or mil-p-16232, type z, class 1 military specification single
treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5305-00-514-0383

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-p-16232 spec.