NSN 5305-00-514-6725

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-514-6725 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.344 inches **Fastener Length:** 1.312 inches **Head Style:** Knurled no. 1 **Head Diameter:** 0.562 inches **Head Height:** 0.312 inches **First Diameter From Head:** Between 0.309 inches and 0.311 inches **Second Diameter From Head:** Between 0.140 inches and 0.150 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.344 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.968 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Qq-s-764 cond a federal specification single material response **Surface Treatment: Passivate Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-00-514-6725

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0