NSN 5305-00-514-7569

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-514-7569 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.366 inches and 0.416 inches **Fastener Length:** Between 0.814 inches and 0.844 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.510 inches and 0.564 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.375 inches **Grip Length:** Between 0.428 inches and 0.438 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 132000 pounds per square inch Hardness Rating: 46.0 rockwell c and 50.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads Material: Steel comp h11 **Material Specification:** Ams6485 assn standard single material response or ams6487 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Nas672 assn standard single treatment response **Thread Series Designator:** Unjf

Shelf Life: N/a

NSN 5305-00-514-7569

Close Tolerance Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0