NSN 5305-00-514-7656

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-514-7656 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.453 inches **Fastener Length:** Between 0.813 inches and 0.843 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.612 inches and 0.672 inches **Grip Diameter:** Between 0.4360 inches and 0.4370 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.437 inches **Grip Length:** Between 0.365 inches and 0.385 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 132000 pounds per square inch Hardness Rating: 46.0 rockwell c and 50.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads Material: Steel comp h11 **Material Specification:** Ams 6485 assn standard single material response or ams 6487 assn standard single material response **Surface Treatment:** Cadmium or nickel **Surface Treatment Specification:** Ams 2416 federal specification single treatment response **Thread Series Designator:**

Unjf

Shelf Life:

N/a

NSN 5305-00-514-7656

Close Tolerance Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0