NSN 5305-00-515-2587

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-515-2587
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.188 inches
Fastener Length:
0.750 inches
Head Style:
Pan no. 2
Head Diameter:
0.562 inches
Head Height:
0.218 inches
Shoulder Diameter:
0.429 inches first shoulder and 0.432 inches first shoulder
Shoulder Length:
0.510 inches first shoulder and 0.511 inches first shoulder
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.375 inches
Features Provided:
Casehardened
Thready Qty Per Inch (tpi):
24
Hardness Rating:
88.3 rockwell superficial 15-n
Shoulder Shape:
Round first shoulder
Special Features:
Thread relief 0.062 in. W/ 0.055 in. Deep
Material:
Steel comp 1018 or steel comp 1022
Material Specification:
Qq-s-631 federal specification 1st material response or qq-s-634 federal specification 1st material response or qq-s-630 federal
specification 1st material response or qq-s-630 federal specification 2nd material response or qq-s-631 federal specification 2nd material
response or qq-s-634 federal specification 2nd material response
Surface Treatment:
Phosphate
Thread Series Designator:
Unf
Chalf Life.

N/a

NSN 5305-00-515-2587

Shoulder Screw - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A003b0