NSN 5305-00-515-2829

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-515-2829 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.109 inches **Fastener Length:** Between 0.343 inches and 0.353 inches Point Length: Between 0.203 inches and 0.213 inches **Point Diameter:** Between 0.198 inches and 0.200 inches First Diameter From Head: Between 0.190 inches and 0.200 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.140 inches Point Style: Dog **Internal Drive Style:** Slot **End Application:** Machine gun .50 caliber 1005-00-179-6526 model xm213 and 1005-00-165-4561 model xm218 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 43.0 rockwell d and 47.0 rockwell d **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 1035 **Material Specification:** Qq-s-631 federal specification single material response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-00-515-2829

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0