## NSN 5305-00-515-6926

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-515-6926 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.288 inches and 0.348 inches **Fastener Length:** Between 0.673 inches and 0.703 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.266 inches and 0.286 inches **Shoulder Diameter:** 0.193 inches first shoulder and 0.195 inches first shoulder **Shoulder Length:** 0.315 inches first shoulder and 0.345 inches first shoulder **Internal Drive Style:** Slot **End Application:** W/s: aircraft, c-2a (reprocured); aircraft, tomcat f-14; aircraft, hawkeye e-2c; aircraft, intruder a-6e **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder **Special Features:** Head painted yellow Material: Steel comp 4037 or steel comp 8740 **Surface Treatment:** Paint top of head **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-00-515-6926

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0