NSN 5305-00-515-6935

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-515-6935 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.288 inches and 0.348 inches **Fastener Length:** Between 0.703 inches and 0.733 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.266 inches and 0.286 inches **Shoulder Diameter:** 0.193 inches first shoulder and 0.195 inches first shoulder **Shoulder Length:** 0.345 inches first shoulder and 0.375 inches first shoulder **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Shoulder Shape: Round first shoulder **Special Features:** Head painted maroon color Material: Steel comp 4037 or steel comp 8740 **Surface Treatment:** Paint top of head **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-00-515-6935 Shoulder Screw - Page 2 of 2



Fiig:

A003b0