NSN 5305-00-516-5466



Assembled Washer Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-516-5466 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.532 inches **Fastener Length:** Between 0.594 inches and 0.625 inches **Head Style:** Hexagon **Head Height:** Between 0.096 inches and 0.110 inches Width Between Flats: Between 0.306 inches and 0.312 inches Washer Quantity: **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Primary Washer Outside Diameter:** Between 0.327 inches and 0.338 inches **Primary Washer Style:** Flat internal teeth **Primary Washer Material Thickness:** 0.020 inches Material: Steel comp 1050 primary washer or steel comp 1551 primary washer or steel comp 1552 primary washer or steel comp 1053 primary washer or steel comp 1054 primary washer or steel comp 1055 primary washer or steel comp 1059 primary washer or steel comp 1060 primary washer or steel comp 1561 primary washer or steel comp 1566 primary washer **Material Specification:** Sae assn standard all material responses primary washer **Surface Treatment:** Cadmium or zinc **Thread Series Designator:** Unc Shelf Life: N/a

No

Unit Of Measure:

Demilitarization:

NSN 5305-00-516-5466

Assembled Washer Screw - Page 2 of 2



Fiig:

A003b0