Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-516-5466

2a	
Za Thread Direction:	
Right-hand	
Thread Length:	
0.532 inches	
Fastener Length:	
	es and 0.625 inches
Head Style:	
Hexagon	
Head Height:	
	es and 0.110 inches
Width Between Fla	
	es and 0.312 inches
Washer Quantity:	
1	
Internal Drive Styl	
W/o internal drive	
Thread Diameter:	
0.164 inches	
Thready Qty Per Ir	ch (tpi):
32	
Primary Washer O	utside Diameter:
Between 0.327 inch	es and 0.338 inches
Primary Washer S	yle:
Flat internal teeth	
Primary Washer M	aterial Thickness:
0.020 inches	
Material:	
Steel comp 1050 pr	mary washer or steel comp 1551 primary washer or steel comp 1552 primary washer or steel comp 1053 primary washe
or steel comp 1054	primary washer or steel comp 1055 primary washer or steel comp 1059 primary washer or steel comp 1060 primary
washer or steel con	p 1561 primary washer or steel comp 1566 primary washer
Material Specificat	ion:
Sae assn standard	all material responses primary washer
Surface Treatment	:
Cadmium or zinc	
Thread Series Des	ignator:
Unc	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

NSN 5305-00-516-5466

Assembled Washer Screw - Page 2 of 2

Fiig: A003b0

