NSN 5305-00-516-5996

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-516-5996

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.428 inches and 0.478 inches
Fastener Length:
Between 1.250 inches and 1.280 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.688 inches and 0.755 inches
Grip Diameter:
Between 0.4985 inches and 0.4995 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.500 inches
Grip Length:
Between 0.802 inches and 0.822 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
132000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches threads
Product Name:
Navy special project
Material:
Steel comp h11
Material Specification:
Ams6485 assn standard single material response or ams6487 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Nas672 assn standard single treatment response
Thread Series Designator:
Unif

NSN 5305-00-516-5996

Close Tolerance Screw - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0