NSN 5305-00-518-5304

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-518-5304 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.485 inches and 0.552 inches **Fastener Length:** Between 2.370 inches and 2.417 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.797 inches and 0.842 inches **Grip Diameter:** Between 0.5605 inches and 0.5615 inches **Shank Unthreaded Hole Diameter:** 0.140 inches first hole **Internal Drive Style:** High-torque **Thread Diameter:** 0.562 inches **Grip Length:** Between 1.865 inches and 1.885 inches Thready Qty Per Inch (tpi): 18 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Distance From Head Largest Bearing Surface To Shank Hole Center: 2.246 inches first hole and 2.293 inches first hole **Surface Finish:** 32.0 microinches threads **Product Name:** Navy special project Material: Steel comp 431 **Material Specification:** Aisi assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Passivate 258, fscm 73197 mfr ref single treatment response **Thread Series Designator:**

Unjf

NSN 5305-00-518-5304

Close Tolerance Screw - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0