## NSN 5305-00-518-5712

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-518-5712 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.230 inches and 0.270 inches **Fastener Length:** Between 1.220 inches and 1.260 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.360 inches and 0.400 inches **Head Height:** Between 0.420 inches and 0.460 inches **First Diameter From Head:** Between 0.125 inches and 0.135 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.770 inches and 0.890 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Aisi assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

## NSN 5305-00-518-5712

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0