NSN 5305-00-518-5726

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-518-5726 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.251 inches and 0.301 inches **Fastener Length:** Between 6.636 inches and 6.666 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **Grip Diameter:** Between 0.1365 inches and 0.1375 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.138 inches **Grip Length:** Between 6.365 inches and 6.385 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Surface Finish:** 32.0 microinches threads **Product Name:** Navy special project Material: Iron alloy 660 **Material Specification:** Ams 5737 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification all treatment responses **Thread Series Designator:** Unjc

Specification Data:

80205-nas1131 professional/industrial association standard

NSN 5305-00-518-5726

Close Tolerance Screw - Page 2 of 2



		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0