NSN 5305-00-518-5807

Close Tolerance Screw - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-518-5807

3aInread Direction:Right-handInread Length:Between 0.444 inches and 0.494 inchesFastener Length:Between 1.579 inches and 1.609 inchesHead Style:Flat countersunkHead Diameter:Between 0.497 inches and 0.507 inchesGrip Diameter:Between 0.2490 inches and 0.2495 inchesInternal Drive Style:High-torqueThread Diameter:0.250 inchesGrip Length:Between 1.115 inches and 1.135 inchesThready Qty Per Inch (tpi):28Countersink Angle:Between 99.0 degrees and 101.0 degreesMaterial:Stainless steelSurface Treatment:PassivateThread Series Designator:UnjfShelf Life:NaMaterial:NaFig:A003b0	Thread Class:		
Right-handThread Length:Between 0.444 inches and 0.494 inchesFastener Length:Between 1.579 inches and 1.609 inchesHead Style:Flat countersunkHead Diameter:Between 0.497 inches and 0.507 inchesGrip Diameter:Between 0.2490 inches and 0.2495 inchesInternal Drive Style:High-torqueThread Diameter:0.250 inchesGrip Length:Between 1.115 inches and 1.135 inchesThready Qty Per Inch (tpi):28Countersink Angle:Between 99.0 degrees and 101.0 degreesMaterial:Stainless steelSurface Treatment:PassivateThread Series Designator:UnifNaDemilitarization:NoFilg:Filg:	3a		
Thread Length:Between 0.444 inches and 0.494 inchesFastener Length:Between 1.579 inches and 1.609 inchesHead Style:Flat countersunkHead Diameter:Between 0.497 inches and 0.507 inchesGrip Diameter:Between 0.2490 inches and 0.2495 inchesInternal Drive Style:High-torqueThread Diameter:0.250 inchesGrip Length:Between 1.115 inches and 1.135 inchesThready Qty Per Inch (tpi):28Countersink Angle:Between 99.0 degrees and 101.0 degreesMaterial:Stainless steelSurface Treatment:PassivateThread Series Designator:UnjfShelf Life:N/aUnit Of Measure:Pemilitarization:NoFig:	Thread Direction:		
Between 0.444 inches and 0.494 inches Fastener Length: Between 1.579 inches and 1.609 inches Head Style: Flat countersunk Head Diameter: Between 0.497 inches and 0.507 inches Grip Diameter: Between 0.2490 inches and 0.2495 inches Internal Drive Style: High-torque Thread Diameter: 0.250 inches Grip Length: Between 1.115 inches and 1.135 inches Thready Qty Per Inch (tpi): 28 Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Right-hand		
Fastener Length:Between 1.579 inches and 1.609 inchesHead Style:Flat countersunkHead Diameter:Between 0.497 inches and 0.507 inchesGrip Diameter:Between 0.2490 inches and 0.2495 inchesInternal Drive Style:High-torqueThread Diameter:0.250 inchesGrip Length:Between 1.115 inches and 1.135 inchesThready Qty Per Inch (tpi):28Countersink Angle:Between 99.0 degrees and 101.0 degreesMaterial:Stainless steelSurface Treatment:PassivateThread Series Designator:UnjfShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:	Thread Length:		
Between 1.579 inches and 1.609 inches Head Style: Flat countersunk Head Diameter: Between 0.497 inches and 0.507 inches Grip Diameter: Between 0.2490 inches and 0.2495 inches Internal Drive Style: High-torque Thread Diameter: 0.250 inches Grip Length: Between 1.115 inches and 1.135 inches Thready Qty Per Inch (tpi): 28 Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: T Demilitarization: No Fiig:	Between 0.444 inches and 0.494 inc	nes	
Head Style:Flat countersunkHead Diameter:Between 0.497 inches and 0.507 inchesGrip Diameter:Between 0.2490 inches and 0.2495 inchesInternal Drive Style:High-torqueThread Diameter:0.250 inchesGrip Length:Between 1.115 inches and 1.135 inchesThready Qty Per Inch (tpi):28Countersink Angle:Between 99.0 degrees and 101.0 degreesMaterial:Stainless steelSurface Treatment:PassivateThread Series Designator:UnjfShelf Life:NaPine Of Measure:-Demilitarization:NoFlig:	Fastener Length:		
Flat countersunk Head Diameter: Between 0.497 inches and 0.507 inches Grip Diameter: Between 0.2490 inches and 0.2495 inches Internal Drive Style: High-torque Thread Diameter: 0.250 inches Grip Length: Between 1.115 inches and 1.135 inches Thready Qty Per Inch (tpi): 28 Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Between 1.579 inches and 1.609 inc	nes	
Head Diameter: Between 0.497 inches and 0.507 inches Grip Diameter: Between 0.2490 inches and 0.2495 inches Internal Drive Style: High-torque Thread Diameter: 0.250 inches Grip Length: Between 1.115 inches and 1.135 inches Thready Qty Per Inch (tpi): 28 Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No	Head Style:		
Between 0.497 inches and 0.507 inches Grip Diameter: Between 0.2490 inches and 0.2495 inches Internal Drive Style: High-torque Thread Diameter: 0.250 inches Grip Length: Between 1.115 inches and 1.135 inches Thready Qty Per Inch (tpi): 28 Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Stainless steel Stainless steel Surface Treatment: Passivate Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No	Flat countersunk		
Grip Diameter: Between 0.2490 inches and 0.2495 inches Internal Drive Style: High-torque Thread Diameter: 0.250 inches Grip Length: Between 1.115 inches and 1.135 inches Thready Qty Per Inch (tpi): 28 Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Stainless steel Stainless steel Surface Treatment: Passivate Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No	Head Diameter:		
Between 0.2490 inches and 0.2495 inches Internal Drive Style: High-torque Thread Diameter: 0.250 inches Grip Length: Between 1.115 inches and 1.135 inches Thready Qty Per Inch (tpi): 28 Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unif Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Between 0.497 inches and 0.507 inc	nes	
Internal Drive Style: High-torque Thread Diameter: 0.250 inches Grip Length: Between 1.115 inches and 1.135 inches Thready Qty Per Inch (tpi): 28 Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Grip Diameter:		
High-torque Thread Diameter: 0.250 inches Grip Length: Between 1.115 inches and 1.135 inches Thready Qty Per Inch (tpi): 28 Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unif Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Between 0.2490 inches and 0.2495 i	nches	
Thread Diameter:0.250 inchesGrip Length:Between 1.115 inches and 1.135 inchesThready Qty Per Inch (tpi):28Countersink Angle:Between 99.0 degrees and 101.0 degreesMaterial:Stainless steelSurface Treatment:PassivateThread Series Designator:UnjfShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:	Internal Drive Style:		
0.250 inches Grip Length: Between 1.115 inches and 1.135 inches Thready Qty Per Inch (tpi): 28 Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	High-torque		
Grip Length: Between 1.115 inches and 1.135 inches Thready Qty Per Inch (tpi): 28 Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Pemilitarization: No	Thread Diameter:		
Between 1.115 inches and 1.135 inches Thready Qty Per Inch (tpi): 28 Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.250 inches		
Thready Qty Per Inch (tpi):28Countersink Angle:Between 99.0 degrees and 101.0 degreesMaterial:Stainless steelSurface Treatment:PassivateThread Series Designator:UnjfShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Grip Length:		
28 Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Stainless steel Stainless steel Surface Treatment: Passivate Passivate Thread Series Designator: Unif Shelf Life: N/a Dit Of Measure: Fig:	Between 1.115 inches and 1.135 inc	nes	
Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Stainless steel Surface Treatment: Passivate Passivate Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Fig:	Thready Qty Per Inch (tpi):		
Between 99.0 degrees and 101.0 degrees Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	28		
Material:Stainless steelSurface Treatment:PassivateThread Series Designator:UnjfShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:	Countersink Angle:		
Stainless steel Surface Treatment: Passivate Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Between 99.0 degrees and 101.0 de	grees	
Surface Treatment: Passivate Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material:		
Passivate Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Stainless steel		
Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Surface Treatment:		
Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Passivate		
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Thread Series Designator:		
N/a Unit Of Measure: Demilitarization: No Fiig:	Unjf		
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:		
 Demilitarization: No Fiig:	N/a		
Demilitarization: No Fiig:	Unit Of Measure:		
No Fiig:			
Fiig:	Demilitarization:		
-	No		
A003b0	Fiig:		
	A003b0		