NSN 5305-00-519-6530

Setscrew - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-519-6530



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.240 inches and 0.260 inches Fastener Length: Between 0.390 inches and 0.410 inches **Head Style:** Double hexagon extended washer **Head Height:** Between 0.320 inches and 0.340 inches Width Between Flats: Between 0.304 inches and 0.313 inches **Extended Washer Diameter:** Between 0.428 inches and 0.448 inches **Extended Washer Thickness:** Between 0.060 inches and 0.070 inches **Point Length:** Between 0.130 inches and 0.170 inches **Point Style:** Ball **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 42.0 rockwell c and 46.0 rockwell c Material: Steel comp 601 Surface Treatment: Nickel and cadmium Surface Treatment Specification: Ams 2416 assn standard all treatment responses **Thread Series Designator:** Unjf Shelf Life: N/a Unit Of Measure:

NSN 5305-00-519-6530

Setscrew - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

