## NSN 5305-00-519-7513

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-519-7513 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.206 inches and 0.301 inches **Fastener Length:** Between 0.297 inches and 0.342 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.231 inches and 0.279 inches **Head Height:** 0.041 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 125000 pounds per square inch **Countersink Angle:** 100.0 degrees **Screw Material:** Steel comp 431 **Screw Material Specification:** Aisi assn standard single material response **Screw Surface Treatment:** Oxide **Screw Surface Treatment Specification:** Mil-c-13924, cl 2 military specification single treatment response **Special Features:** Furnished with one o-ring and plastic flat washer **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 5305-00-519-7513

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-c-13924 spec.