## NSN 5305-00-522-0440

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-522-0440 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.357 inches and 0.438 inches **Fastener Length:** Between 0.407 inches and 0.438 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.058 inches and 0.068 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Primary Washer Outside Diameter:** Between 0.220 inches and 0.230 inches **Primary Washer Style:** Flat external teeth **Primary Washer Material Thickness:** Between 0.012 inches and 0.020 inches **Product Name:** Navy special project Material: Steel comp 303 **Material Specification:** Qq-s-764 cond a federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc

Shelf Life: N/a

## NSN 5305-00-522-0440

Assembled Washer Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0