

View Online at <https://aerobasegroup.com/nsn/5305-00-522-2437>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.328 inches

**Fastener Length:**

0.750 inches

**Head Style:**

Pan no. 2

**Head Diameter:**

0.563 inches

**Head Height:**

0.125 inches

**Shank Unthreaded Hole Diameter:**

0.078 inches first hole

**First Diameter From Head:**

0.313 inches

**Second Diameter From Head:**

0.375 inches

**Third Diameter From Head:**

0.281 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.063 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

0.359 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

0.750 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

152.0 brinell standard and 219.0 brinell standard

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.594 inches first hole

**Externally Relieved Body Diameter Quantity:**

3

**Material:**

Steel

**Surface Treatment:**

Phosphate

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0