NSN 5305-00-522-9607

Close Tolerance Screw - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-522-9607

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.381 inches and 0.431 inches |
| Fastener Length: |
| Between 1.391 inches and 1.421 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.376 inches and 0.385 inches |
| Grip Diameter: |
| Between 0.1890 inches and 0.1895 inches |
| Shank Unthreaded Hole Diameter: |
| 0.070 inches first hole and 0.075 inches first hole |
| Internal Drive Style: |
| High-torque |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 0.990 inches and 1.010 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Distance From Head Largest Bearing Surface To Shank Hole Center: |
| 1.270 inches first hole and 1.310 inches first hole |
| Material: |
| Stainless steel |
| Surface Treatment: |
| Passivate |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A003b0 |
| |