NSN 5305-00-525-2089

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-525-2089 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 1.750 inches **Fastener Length:** 2.312 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.308 inches and 0.332 inches First Diameter From Head: Between 0.141 inches and 0.164 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.490 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** 100.0 degrees **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 1008 or steel comp 1010 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1020 or steel comp 1021 or steel comp 1022 **Material Specification:** 66 federal standard all material responses or aisi/sae assn standard all material responses **Surface Treatment:** Cadmium **Surface Treatment Specification:** Jh ps 2201 fscm 31435 mfr ref single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

No

Unit Of Measure:

Demilitarization:

NSN 5305-00-525-2089

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0