

View Online at <https://aerobasegroup.com/nsn/5305-00-526-0767>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.359 inches and 0.391 inches

Fastener Length:

1.125 inches

Head Style:

Knurled no. 1

Head Diameter:

Between 0.432 inches and 0.442 inches

Head Height:

Between 0.234 inches and 0.266 inches

First Diameter From Head:

Between 0.115 inches and 0.125 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.734 inches and 0.766 inches

Internal Drive Style:

Slot

Thread Diameter:

0.164 inches

Thready Qty Per Inch (tpi):

32

Criticality Code Justification:

Zzzy

Externally Relieved Body Diameter Quantity:

1

Special Features:

Item must comply with requirements of defense supply center philadelphia production standard no. Po0144nrp

Material:

Steel comp 303

Material Specification:

Astm a582 assn standard single material response

Surface Treatment:

Passivate

Special Test Features:

Special quality control testing

Surface Treatment Specification:

Mil-f-14072, finish e300 military specification single treatment response

Test Data Document:

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Reference Number Differentiating Characteristics:

Reference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.