## NSN 5305-00-526-2356

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-526-2356

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.945 inches and 1.000 inches
Fastener Length:
Between 0.970 inches and 1.000 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.091 inches and 0.096 inches
Head Height:
Between 0.057 inches and 0.060 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.060 inches
Width Across Flats:
Between 0.050 inches and 0.051 inches
Thready Qty Per Inch (tpi):
80
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Minimum Yield Strength:
30000 pounds per square inch
Material:
Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unrf
Specification Data:
80205-nas1351 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

## NSN 5305-00-526-2356

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0