NSN 5305-00-527-3916

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-527-3916 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.210 inches **Fastener Length:** Between 0.219 inches and 0.250 inches **Head Style:** Fillister **Head Diameter:** Between 0.187 inches and 0.205 inches **Head Height:** Between 0.078 inches and 0.088 inches Washer Quantity: **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.125 inches Thready Qty Per Inch (tpi): 40 **Primary Washer Outside Diameter:** Between 0.183 inches and 0.196 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** 0.020 inches Material: Steel comp 1010 fastener or steel comp 1011 fastener or steel comp 1013 fastener or steel comp 1015 fastener or steel comp 1016 fastener or steel comp 1017 fastener or steel comp 1018 fastener or steel comp 1019 fastener or steel comp 1020 fastener **Surface Treatment:** Cadmium or zinc **Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-00-527-3916

Assembled Washer Screw - Page 2 of 2



Fiig:

A003b0