Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-527-5480

iew Online at https://aerobasegroup.com/nsn/3303-00-327-3460
hread Class:
hread Direction:
ight-hand
hread Length:
.344 inches
astener Length:
.094 inches
ead Style:
nurled no. 1
ead Diameter:
.500 inches
ead Height:
.188 inches
irst Diameter From Head:
etween 0.235 inches and 0.245 inches
econd Diameter From Head:
150 inches
istance From Largest Bearing Surface Of Head To End Of First Diameter:
.141 inches
istance From Largest Bearing Surface Of Head To End Of Second Diameter:
.609 inches
nternal Drive Style:
ross recess type 1
hread Diameter:
.250 inches
hready Qty Per Inch (tpi):
0
lin. Tensile Strength (psi):
5000 pounds per square inch
xternally Relieved Body Diameter Quantity:
laterial:
teel comp 304
laterial Specification:
eq-s-763 federal specification single material response
urface Treatment:
assivate
hread Series Designator:
helf Life:
la
1a

NSN 5305-00-527-5480

Externally Relieved Body Screw - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0