## NSN 5305-00-528-4724

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-528-4724 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.277 inches and 0.328 inches **Fastener Length:** Between 1.231 inches and 1.251 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.477 inches and 0.492 inches **Head Height:** Between 0.126 inches and 0.141 inches **Grip Diameter:** Between 0.2487 inches and 0.2492 inches **Shank Unthreaded Hole Diameter:** 0.076 inches first hole and 0.086 inches first hole **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.812 inches and 0.828 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 1.145 inches first hole and 1.161 inches first hole **Surface Finish:** 63.0 microinches bearing surface of head **Special Features:** Retaining balls in shank Material: Steel **Surface Treatment: Passivate Thread Series Designator:** Unjf

Shelf Life:

N/a

## NSN 5305-00-528-4724

Close Tolerance Screw - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0