NSN 5305-00-528-5293

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-528-5293 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.422 inches and 0.516 inches **Fastener Length:** Between 0.484 inches and 0.516 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.303 inches and 0.312 inches **Head Height:** Between 0.185 inches and 0.190 inches **Hole Diameter:** Between 0.044 inches and 0.050 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.156 inches and 0.159 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 80000 pounds per square inch **Hardness Rating:** 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch **Hole Configuration Style:** Round longitudinal hole Material: Steel comp xm-7 or steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 **Surface Treatment: Passivate**

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

NSN 5305-00-528-5293

Socket Head Cap Screw - Page 2 of 2



Thread Series Designator:
Unrf
Specification Data:
80205-nas1351 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0