NSN 5305-00-528-5675

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-528-5675 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.108 inches and 0.169 inches **Fastener Length:** Between 0.158 inches and 0.188 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.105 inches and 0.119 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.060 inches Thready Qty Per Inch (tpi): 80 Min. Tensile Strength (psi): 55000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Navy special project **Screw Material:** Copper alloy 360 **Screw Material Specification:** Qq-b-626, 1/2 h federal specification single material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unf **Specification Data:** 80205-nas662 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5305-00-528-5675

Machine Screw - Page 2 of 2



Fiig:

A500d0