NSN 5305-00-529-9899

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-529-9899 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.325 inches and 0.416 inches **Fastener Length:** Between 1.083 inches and 1.103 inches **Head Style:** Pan **Head Diameter:** Between 0.475 inches and 0.495 inches **Head Height:** Between 0.165 inches and 0.185 inches **First Diameter From Head:** Between 0.225 inches and 0.245 inches **Second Diameter From Head:** Between 0.180 inches and 0.200 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.083 inches and 0.103 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.594 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 **Material Specification:** 66 federal standard all material responses or aisi assn standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5305-00-529-9899

Externally Relieved Body Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0