Externally Relieved Body Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-529-9899

Threa	ad Class:
3a	
Threa	ad Direction:
Right	-hand
Threa	ad Length:
Betw	een 0.325 inches and 0.416 inches
Faste	ener Length:
Betw	een 1.083 inches and 1.103 inches
Head	I Style:
Pan	
Head	I Diameter:
Betw	een 0.475 inches and 0.495 inches
Head	I Height:
Betw	een 0.165 inches and 0.185 inches
First	Diameter From Head:
Betw	een 0.225 inches and 0.245 inches
Seco	nd Diameter From Head:
Betw	een 0.180 inches and 0.200 inches
Dista	nce From Largest Bearing Surface Of Head To End Of First Diameter:
Betwo	een 0.083 inches and 0.103 inches
Dista	nce From Largest Bearing Surface Of Head To End Of Second Diameter:
0.594	l inches
Interi	nal Drive Style:
Cross	s recess type 1
Threa	ad Diameter:
0.250	) inches
Threa	ady Qty Per Inch (tpi):
28	
Exter	rnally Relieved Body Diameter Quantity:
1	
Mate	rial:
Steel	comp 302 or steel comp 303 or steel comp 304 or steel comp 305
Mate	rial Specification:
66 fe	deral standard all material responses or aisi assn standard all material responses
Surfa	ace Treatment:
Passi	ivate
Surfa	ace Treatment Specification:
Qq-p	-35 federal specification single treatment response
Threa	ad Series Designator:
Unjf	
Shelf	f Life:
N/a	

Externally Relieved Body Screw - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0