NSN 5305-00-530-3339

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-530-3339

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.284 inches and 0.290 inches |
| Fastener Length: |
| 0.625 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.302 inches and 0.322 inches |
| Head Height: |
| Between 0.099 inches and 0.119 inches |
| Shoulder Diameter: |
| 0.247 inches first shoulder and 0.248 inches first shoulder |
| Shoulder Length: |
| 0.227 inches first shoulder and 0.233 inches first shoulder |
| Shank Unthreaded Hole Diameter: |
| 0.052 inches first hole |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.190 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Hardness Rating: |
| 45.0 rockwell c and 55.0 rockwell c |
| Distance From Head Largest Bearing Surface To Shank Hole Center: |
| 0.500 inches first hole |
| Shoulder Shape: |
| Round first shoulder |
| Special Features: |
| 0.242 in. Diameter by 0.031 in. Head relief |
| Material: |
| Steel |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5305-00-530-3339

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0