

View Online at <https://aerobasegroup.com/nsn/5305-00-530-6167>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.381 inches and 0.431 inches

Fastener Length:

Between 0.891 inches and 0.921 inches

Head Style:

Flat countersunk

Head Diameter:

0.3813 inches

Grip Diameter:

Between 0.1885 inches and 0.1895 inches

Internal Drive Style:

High-torque

Thread Diameter:

0.190 inches

Grip Length:

Between 0.490 inches and 0.510 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Surface Finish:

32.0 microinches threads

Material:

Steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 4130 or steel comp 6150

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6758 military specification 5th material response or mil-s-8503 military specification 6th material response

Surface Treatment:

Cadmium head and primer head

Surface Treatment Specification:

Qq-p-416, type 2 class 2 federal specification 1st treatment response head and ps 13421 fscm 76301 mfr ref 2nd treatment response head

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.