NSN 5305-00-530-9493

Externally Relieved Body Screw - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5305-00-530-9493 |
|--|
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.500 inches |
| Fastener Length: |
| 1.250 inches |
| Head Style: |
| Binding |
| Head Diameter: |
| 0.312 inches |
| Head Height: |
| 0.109 inches |
| First Diameter From Head: |
| 0.164 inches |
| Second Diameter From Head: |
| 0.117 inches |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| 0.047 inches |
| Distance From Largest Bearing Surface Of Head To End Of Second Diameter: |
| 0.750 inches |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.164 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Externally Relieved Body Diameter Quantity: |
| 1 |
| Product Name: |
| Navy special project |
| Material: |
| Steel comp 303 |
| Material Specification: |
| Astm a582 assn standard all material responses |
| Surface Treatment: |
| Passivate |
| Thread Series Designator: |
| Unc |
| Shelf Life: |

N/a

NSN 5305-00-530-9493

Externally Relieved Body Screw - Page 2 of 2



| | | | ure: | |
|--|--|--|------|--|
| | | | | |
| | | | | |

--

Demilitarization:

No

Fiig:

A003b0