## NSN 5305-00-530-9739



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-530-9739 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.250 inches and 0.312 inches **Fastener Length:** Between 0.281 inches and 0.312 inches **Head Style:** Fillister **Head Diameter:** Between 0.208 inches and 0.226 inches **Head Height:** Between 0.089 inches and 0.096 inches **Hole Diameter:** 0.046 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches **Hole Quantity:** 1 Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 60000 pounds per square inch **Screw Material:** Steel comp 1010 or steel comp 1015 or steel comp 1016 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1022 or steel comp 1025 or steel comp 1026 or steel comp 1035 or steel comp 1040 or steel comp 1042 or steel comp 1045 or steel comp 1046 or steel comp 1548 or steel comp 1049 or steel comp 1050 **Screw Surface Treatment:** Cadmium or zinc **Screw Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification 1st treatment response or qq-z-325, type 2, cl 3 federal specification 2nd treatment response **Head Hole Configuration Style:** Round **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## **NSN 5305-00-530-9739** Machine Screw - Page 2 of 2



Fiig:

A500d0