

View Online at <https://aerobasegroup.com/nsn/5305-00-530-9777>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.714 inches and 0.750 inches

Fastener Length:

0.750 inches

Head Style:

Fillister

Head Diameter:

Between 0.124 inches and 0.140 inches

Head Height:

Between 0.055 inches and 0.062 inches

Hole Diameter:

0.031 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.086 inches

Hole Quantity:

1

Thready Qty Per Inch (tpi):

56

Min. Tensile Strength (psi):

60000 pounds per square inch

Screw Material:

Steel comp 1010 or steel comp 1015 or steel comp 1016 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1022 or steel comp 1025 or steel comp 1026 or steel comp 1035 or steel comp 1040 or steel comp 1042 or steel comp 1045 or steel comp 1046 or steel comp 1548 or steel comp 1049 or steel comp 1050

Screw Surface Treatment:

Cadmium or zinc

Screw Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification 1st treatment response or qq-z-325, type 2, cl 3 federal specification 2nd treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0