## NSN 5305-00-530-9789

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-530-9789

view offilite at https://aerobasegroup.com/hist//0500-00-550-5705
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.276 inches and 0.312 inches
Fastener Length:
Between 0.281 inches and 0.312 inches
Head Style:
Fillister
Head Diameter:
Between 0.124 inches and 0.140 inches
Head Height:
Between 0.055 inches and 0.062 inches
Hole Diameter:
0.031 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.086 inches
Hole Quantity:
1
Thready Qty Per Inch (tpi):
56
Min. Tensile Strength (psi):
60000 pounds per square inch
Screw Material Specification:
Qq-s-630 federal specification 1st material response or qq-s-631 federal specification 2nd material response or qq-w-405 federal
specification 3rd material response or qq-s-634 federal specification 4th material response
Screw Surface Treatment:
Cadmium or zinc
Screw Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification 1st treatment response or qq-z-325, type 2, cl 3 federal specification 2nd treatment response
Head Hole Configuration Style:
Round
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## **NSN 5305-00-530-9789** Machine Screw - Page 2 of 2



Fiig:

A500d0