Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-531-0139

Thread Cla	SS:
2a	
Thread Dire	action:
Right-hand	
Thread Len	
0.312 inche	
Fastener Lo	
0.438 inche	
Head Style	
Fillister	
Head Diam	
	389 inches and 0.414 inches
Head Heigh	
Between 0.7	155 inches and 0.170 inches
Washer Qu	antity:
1	
Internal Dri	ve Style:
Cross reces	s type 1
Thread Dia	meter:
0.250 inche	S
Thready Qt	y Per Inch (tpi):
20	
Hardness F	Rating:
45.0 rockwe	Il c primary washer and 53.0 rockwell c primary washer
Primary Wa	isher Outside Diameter:
Between 0.3	384 inches and 0.400 inches
Primary Wa	isher Style:
Split helical	ring
Primary Wa	isher Material Thickness:
0.063 inche	S
Surface Tre	eatment:
Cadmium c	r zinc
Surface Tre	eatment Specification:
Qq-p-416, 1	ype 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response
Thread Ser	ies Designator:
Unc	
Shelf Life:	
N/a	
Unit Of Mea	asure:
Demilitariza	ation:
No	

NSN 5305-00-531-0139

Assembled Washer Screw - Page 2 of 2

Fiig: A003b0

