NSN 5305-00-531-3968

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-531-3968 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.504 inches and 0.571 inches **Fastener Length:** Between 0.952 inches and 0.999 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.629 inches and 0.634 inches **Grip Diameter:** Between 0.3115 inches and 0.3120 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 95000 pounds per square inch **Hardness Rating:** 24.0 rockwell c and 44.0 rockwell c **Countersink Angle:** 100.0 degrees **Surface Finish:** 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams 5736 assn standard single material response **Thread Series Designator:** Unf Shelf Life: **Unit Of Measure:**

N/a
Unit Of Measure:
-Demilitarization:
No

NSN 5305-00-531-3968

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0