## NSN 5305-00-533-7013

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-533-7013 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.246 inches and 0.286 inches **Fastener Length:** Between 0.662 inches and 0.682 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **First Diameter From Head:** Between 0.077 inches and 0.097 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.396 inches and 0.416 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Product Name:** Navy special project Material: Steel comp 302 or steel comp 304 or steel comp 305 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

## NSN 5305-00-533-7013

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0