## NSN 5305-00-533-9472

Between 0.277 inches and 0.328 inches

Between 2.543 inches and 2.563 inches

**Thread Class:** 

Right-hand

Thread Length:

**Thread Direction:** 

Fastener Length:

Crowned hexagon
Head Height:

**Head Style:** 

За

Close Tolerance Screw - Page 1 of 2



 $\label{thm:com/nsn/5305-00-533-9472} View \ Online \ at \ https://aerobasegroup.com/nsn/5305-00-533-9472$ 

Between 0.126 inches and 0.141 inches
Width Between Flats:
Between 0.430 inches and 0.439 inches
Locking Feature:
Detent ball grip
Grip Diameter:
Between 0.2487 inches and 0.2492 inches
Internal Drive Style:
Slot
Thread Diameter:
0.250 inches
Grip Length:
Between 2.125 inches and 2.141 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
63000 pounds per square inch
Surface Finish:
32.0 microinches grip
Special Features:
Retaining element in shank
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf

## NSN 5305-00-533-9472

Close Tolerance Screw - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0