NSN 5305-00-536-6822

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-536-6822 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.306 inches and 0.357 inches **Fastener Length:** Between 1.728 inches and 1.748 inches **Head Style:** Crowned hexagon **Head Height:** Between 0.157 inches and 0.172 inches Width Between Flats: Between 0.492 inches and 0.502 inches **Grip Diameter:** Between 0.3112 inches and 0.3117 inches **Shank Unthreaded Hole Diameter:** 0.076 inches first hole and 0.086 inches first hole **Internal Drive Style:** Slot **Thread Diameter:** 0.312 inches **Grip Length:** Between 1.250 inches and 1.266 inches Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Center: 1.625 inches first hole Surface Finish: 32.0 microinches grip **Special Features:** Retaining element in shank Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response

Unjf

Thread Series Designator:

NSN 5305-00-536-6822

Close Tolerance Screw - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0