## NSN 5305-00-536-6826

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-536-6826

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length: Between 0.306 inches and 0.357 inches
Fastener Length:
Between 2.228 inches and 2.248 inches
Head Style:
Crowned hexagon
Head Height:
Between 0.157 inches and 0.172 inches
Width Between Flats:
Between 0.492 inches and 0.502 inches
Grip Diameter:
Between 0.3112 inches and 0.3117 inches
Shank Unthreaded Hole Diameter:
0.076 inches first hole and 0.086 inches first hole
Internal Drive Style:
Slot
Thread Diameter:
0.312 inches
Grip Length:
Between 1.750 inches and 1.766 inches
Thready Qty Per Inch (tpi):
24
Distance From Head Largest Bearing Surface To Shank Hole Center:
2.115 inches first hole and 2.135 inches first hole
Surface Finish:
32.0 microinches grip
Special Features:
Retaining element in shank
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf

## NSN 5305-00-536-6826

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

